

**Report 10357
Final
20 November 1994**

**Earth Observing System (EOS)
Advanced Microwave Sounding Unit-A (AMSU-A)
Worst-Case Analysis - Antenna Beam Pointing**

**Contract No: NAS 5-32314
CDRL: 112B**

Submitted to:

**National Aeronautics and Space Administration
Goddard Space Flight Center
Greenbelt, Maryland 20771**

Submitted by:

**Aerojet
1100 West Hollyvale Street
Azusa, California 91702**

INTRODUCTION

This report is provided in partial fulfillment of the requirement for worst-case analyses of the Advanced Microwave Sounding Unit-A to be flown on the Earth Observing System (EOS/AMSU-A). It is submitted in response to Contract NAS5-32314, CDRL Item 112.

Presented is a worst-case analysis of the EOS/AMSU-A Beam Pointing. Two worst-case analyses addressing an in-orbit calibration accuracy analysis and an in-orbit radiometer sensitivity (NEAT) analysis were provided under a separate cover (Aerojet Report No. 10471).

WORST-CASE ANALYSIS - ANTENNA BEAM POINTING FOR EOS/AMSU-A

Requirement

The EOS/AMSU-A beam pointing requirements are given in GSFC-422-12-12-01, Performance and Operation Specification for the Advanced Microwave Sounding Unit-A. The specification states that for each beam position, in both the scan (cross-track) and the spacecraft velocity (down-track) directions, the beam pointing accuracy for each beam shall be better than $\pm 0.2^\circ$.

Analysis

There are three sources of beam pointing error. These are mechanical tolerances in the manufacture and assembly of the parts, allowable axial displacement of the reflector relative to the motor shaft, and on-orbit thermal distortions. For the worst-case analysis, each will be assumed to act independently and thus each contribution is additive.

The mechanical tolerance analysis was completed using the NOAA/AMSU-A drawings as references. For the A2 module, the NOAA/AMSU-A drawing details relating to beam pointing will remain unchanged for the EOS/AMSU-A configuration. For the A1 module, the spacecraft mounting surface will be changed from the NOAA/AMSU-A side-mounted system to the EOS/AMSU-A base mount. However, the mechanical assembly and machining steps are expected to be similar to those used for the NOAA/AMSU-A1 module. Detailed calculations for the mechanical errors are shown in Figures 1 and 2 for the A1 and A2 modules, respectively.

The key to controlling the mechanical tolerances to acceptable beam pointing limits is in the assembly sequence of the structure. The primary structures of both modules are assembled to a level termed the machined antenna subassembly. For the NOAA/AMSU-A configurations, the A1 subassembly is detailed on Drawing 1331351, while the corresponding A2 subassembly is described on Drawing 1331303. The structural parts that will be removed at higher levels of assembly are match-drilled and pinned to the subassembly. The interfaces most affecting alignment are machined on the subassembly. These are the spacecraft mounting interface, the motor drive mounting interfaces, and the alignment cube interface. In this manner, the tolerance build-ups of the individual parts are eliminated at the subassembly.

The sources of error will be explained in the order of presentation in Table I. The first three errors are associated with the alignment cube. The first is the error in the surface (wave) of the alignment cube optical surface. The second is the error in locating the optical surface relative to the cube mounting surface. This error is attributable to the fabrication of the cube. The third error is the result of the machining accuracy of the cube mounting surface on the machined antenna subassembly.

The motor mount error is the machining error in establishing the motor mount surface on the machined antenna subassembly. As shown in Figure 1, the error was calculated for both the upper motor mount and the lower motor mount. The worst case from these calculations was entered in Table I. The motor shaft error is the allowable shaft run-out error relative to the motor mounting surface. At this assembly, the motor bearings and shaft are installed in the housing, and the mounting surface of the housing is machined relative to the shaft.

The reflector tolerance refers to the location of the parabolic surface of the antenna relative to the hub that interfaces with the motor shaft. The locating pin position refers to the dowel pin positions on the interface. Each module has two dowel pins for locating the instrument. For NOAA/AMSU-A, the A1 pin positions add to the down-track error. For the EOS/AMSU-A configurations the locating pin errors for both the A1 and A2 modules contribute to the cross-track pointing error. The final mechanical tolerance is the accuracy of machining the spacecraft interface relative to the cube surface and the motor mounting surfaces. The error is controlled at the machined subassembly level.

Relative axial movement of the antenna along the motor shaft will cause the illumination distribution of the reflector relative to the feedhorn to change. This has a minimum effect on the down-track beam pointing error, and no measurable effect on cross-track beam pointing error. The down-track error functions are shown in Figures 3 and 4 for the A1 and A2 modules, respectively. The allowable movement of the antenna along the motor shaft is 0.015 inch. This is verified by measurements taken before and after structural tests. The worst-case beam shift at ± 0.015 inch was entered in Table I.

The final contribution to beam pointing error results from thermal distortions that may occur on orbit. Since detailed thermal analyses cannot be undertaken until the EOS spacecraft is defined, the thermal distortion has only been budgeted at this time. The beam-pointing error is based on an assumed 10°C thermal gradient from the mounting surface to the motor drive mounting surface. The effect of the gradient is estimated by assuming that the structure at the height of the motor mounting surface is stationary and that the aluminum mounting surface changes by 10°C. The thermal distortion at the base divided by the distance to the motor mounting surface gives the slope of the beam pointing error.

Summary

As shown in Table I, the worst-case beam-pointing errors for both the A1 and A2 modules are less than the required 0.2 degree.

Table I Worst-Case Beam-pointing Error

Source of Error	Error in Degrees	
	A 1	A 2
Cube Surface Finish	0.005	0.005
Cube Perpendicularity	0.022	0.022
Cube Mounting Accuracy	0.044	0.044
Motor Mount Tolerance	0.008	0.006
Motor Shaft Tolerance	0.010	0.044
Reflector Tolerance	0.030	0.029
Locating Pin Position	0.025	0.017
Interface Tolerance	<u>0.024</u>	<u>0.005</u>
Mechanical Tolerance	0.168	0.173
Reflector/Shaft Slip	0.009	0.017
Thermal Distortion (10°C)	<u>0.017</u>	<u>0.006</u>
WORST CASE	0.194	0.196
RSS	0.071	0.077




Figure 1 A1 Mechanical Tolerances




Figure 2 A2 Mechanical Tolerances




Figure 3 AMSU-A1 Downtrack Pointing Error 1194-3409M




Figure 4 AMSU-A2 Downtrack Pointing Error 1194-3410M

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank) ---	2. REPORT DATE ---	3. REPORT TYPE AND DATES COVERED ---		
4. TITLE AND SUBTITLE Earth Observing System (EOS)/Advanced Microwave Sounding Unit-A (EOS/AMSU-A), Worst-Case Analysis Antenna Beam Pointing		5. FUNDING NUMBERS NAS 5-32314		
6. AUTHOR(S) Wayne Ely				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Aerojet 1100 W. Hollyvale Azusa, CA 91702		8. PERFORMING ORGANIZATION REPORT NUMBER CDRL 112B 10357 November 1994		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) NASA Goddard Space Flight Center Greenbelt, Maryland 20771		10. SPONSORING/MONITORING AGENCY REPORT NUMBER ---		
11. SUPPLEMENTARY NOTES ---				
12a. DISTRIBUTION/AVAILABILITY STATEMENT ---		12b. DISTRIBUTION CODE ---		
13. ABSTRACT (Maximum 200 words) This report presents a worst-case analysis of the EOS/AMSU-A Antenna beam-pointing accuracy.				
14. SUBJECT TERMS EOS Microwave System			15. NUMBER OF PAGES 11	
			16. PRICE CODE ---	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT SAR	



Report Documentation Page

1. Report No. ---	2. Government Accession No. ---	3. Recipient's Catalog No. ---	
4. Title and Subtitle Earth Observing System (EOS)/Advanced Microwave Sounding Unit-A (EOS/AMSU-A), Worst-Case Analysis Antenna Beam Pointing		5. Report Date November 1994	
7. Author(s) Wayne Ely		6. Performing Organization Code ---	
		8. Performing Organization Report No. 10357 November 1994	
9. Performing Organization Name and Address Aerojet 1100 W. Hollyvale Azusa, CA 91702		10. Work Unit No. ---	
12. Sponsoring Agency Name and Address NASA Goddard Space Flight Center Greenbelt, Maryland 20771		11. Contract or Grant No. NAS 5-32314	
		13. Type of Report and Period Covered Final	
14. Sponsoring Agency Code ---		15. Supplementary Notes ---	
16. ABSTRACT (Maximum 200 words) This report presents a worst-case analysis of the EOS/AMSU-A Antenna beam-pointing accuracy.			
17. Key Words (Suggested by Author(s)) EOS Antenna Beam Pointing		18. Distribution Statement Unclassified — Unlimited	
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No. of pages 11	22. Price ---

NASA FORM 1626 OCT 86

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filing in each block of the form follow. It is important to stay within the lines to meet optical scanning requirements.

Block 1. Agency Use Only (Leave blank)

Block 2. Report Date. Full publication date including day, month, and year, if available (e.g., 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered. State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g., 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, report the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers. To include contract and grant numbers; may include program element number(s), project number(s), tasks number(s), and work unit number(s). Use the following labels:

C	-	Contract	PR	-	Project
G	-	Grant	TA	-	Task
PE	-	Program	WU	-	Work Unit
		Element			Accession No.

Block 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es). Self-explanatory.

Block 8. Performing Organization Report Number. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es). Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Reports Number. (if known).

Block 11. Supplementary Notes. Enter information not included elsewhere such as: Prepared in cooperation with ...; Trans. of ...; To be published in ... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12.a Distribution/Availability Statement. Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g., NOFORN, REL, ITAR).

DOD - See DoDD 5230.24 "Distribution Statement on Technical Documents"

DOE - See authorities.

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12.b Distribution Code.

DOD - Leave blank.

DOE - Enter DOE distribution categories from the standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank.

NTIS - Leave blank.

Block 13. Abstract. Include a brief (Maximum 200 words) factual summary of the most significant information contained in the report.

Block 14. Subject Terms. Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages. Enter the total number of pages.

Block 16. Price Code. Enter appropriate price code (NTIS only).

Block 17 - 19. Security Classifications. Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract. This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.

PREPARATION OF THE REPORT DOCUMENTATION PAGE

The last page of a report facing the third cover is the Report Documentation Page, RDP. Information presented on this page is used in announcing and cataloging reports as well as preparing the cover and title page. Thus, it is important that the information be correct. Instructions for filling in each block of the form are as follows:

Block 1. Report No. NASA report series number, if preassigned.

Block 2. Government Accession No. Leave blank.

Block 3. Recipient's Catalog No. Reserved for use by each report recipient.

Block 4. Title and Subtitle. Typed in caps and lower case with dash or period separating subtitle from title.

Block 5. Report Date. Approximate month and year the report will be published.

Block 6. Performing Organization Code. Leave blank.

Block 7. Authors. Provide full names exactly as they are to appear on the title page. If applicable, the word editor should follow a name.

Block 8. Performing Organization Report No. NASA installation report control number and, if desired, the non-NASA performing organization report control number.

Block 9. Performing Organization Name and Address. Provide affiliation (NASA program office, NASA installation, or contractor name) of authors.

Block 10. Work Unit No. Provide Research and Technology Objectives and Plants (RTOP) number.

Block 11. Contract or Grant No. Provide when applicable.

Block 12. Sponsoring Agency Name and Address. National Aeronautics and Space Administration, Washington, D.C. 20546-0001. If contractor report, add NASA installation or HQ program office.

Block 13. Type of Report and Period Covered. NASA formal report series; for Contractor Report also list type (interim, final) and period covered when applicable.

Block 14. Sponsoring Agency Code. Leave blank.

Block 15. Supplementary Notes. Information not included

elsewhere: affiliation of authors if additional space is required for Block 9, notice of work sponsored by another agency, monitor of contract, information about supplements (file, data tapes, etc.) meeting site and date for presented papers, journal to which an article has been submitted, note of a report made from a thesis, appendix by author other than shown in Block 7.

Block 16. Abstract. The abstract should be informative rather than descriptive and should state the objectives of the investigation, the methods employed (e.g., simulation, experiment, or remote sensing), the results obtained, and the conclusions reached.

Block 17. Key Words. Identifying words or phrases to be used in cataloging the report.

Block 18. Distribution Statement. Indicate whether report is available to public or not. If not to be controlled, use "Unclassified-Unlimited." If controlled availability is required, list the category approved on the Document Availability Authorization Form (see NHB 2200.2, Form FF427). Also specify subject category (see "Table of Contents" in a current issue of STAR) in which report is to be distributed.

Block 19. Security Classification (of the report). Self-explanatory.

Block 20. Security Classification (of this page). Self-explanatory.

Block 21. No. of Pages. Count front matter pages beginning with iii, text pages including internal blank pages, and the RDP, but not the title page or the back of the title page.

Block 22. Price Code. If Block 18 shows "Unclassified-Unlimited," provide the NTIS price code (see "NTIS Price Schedules" in a current issue of STAR) and at the bottom of the form add either "For sale by the National Technical Information Service, Springfield, VA 22161-2171" or "For sale by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402-0001," whichever is appropriate.